



Specification:

Heavy-duty hydraulic jacks of the ECO-Jack XR series do, compared with the ECO-Jack S-series, require an external 700 bar pump for operation. This facilitates and accelerates working in confined conditions and when using several jacks at the time. The compact design without a pump leads to a weight reduction of up to 30% and allows for easy handling for optimal use under extreme conditions. External pumps allow simultaneous operation on several ECO-Jack XR series machine jacks by one person. The ECO-Jack XR series has an integrated spring return system, which always returns the machine lifter automatically to the starting position.

Technical data of hydraulic jacks:

#	01 100 31 01	700 bar	300 ml	25,5 kg
1/	External pump	HH = 129 mm	10000 kg	8000 kg
L x B x H	219 x 277 x 250 mm	#V 3 x 75 mm	A _{min} = 20 mm	LH LH = 45 mm

Please always observe the operating instructions, their safety instructions and local conditions!

#	Part No.	Maximum operating pressure in bar	Oil quantity in the tank / cylinder in ml. Standard oil HLP 32 other oils on request	Weight kg
↑	Maximum stroke in mm	Maximum lifting load with the lifting head in kg	Maximum lifting load with lifting claw in kg	Dimensions in mm L x B x H
A	Insertion height in mm	LH Useable length of lifting claw in mm		#V Adjustment positions Distances in mm