



**Specification:**

Heavy-duty hydraulic jacks of the ECO-Jack XR series do, compared with the ECO-Jack S-series, require an external 700 bar pump for operation. This facilitates and accelerates working in confined conditions and when using several jacks at the time. The compact design without a pump leads to a weight reduction of up to 30% and allows for easy handling for optimal use under extreme conditions. External pumps allow simultaneous operation on several ECO-Jack XR series machine jacks by one person. The ECO-Jack XR series has an integrated spring return system, which always returns the machine lifter automatically to the starting position.

**Technical data of hydraulic jacks:**

#	01 150 31 01	700 bar	OIL	400 ml	44 kg
1/	External pump	HH = 155 mm	15000 kg	12000 kg	
L x B x H	245 x 331 x 316 mm	#V	3 x 97 mm	A	$A_{min} = 25 \text{ mm}$
				LH	LH = 55 mm

**Please always observe the operating instructions, their safety instructions and local conditions!**

#	Part No.	Maximum operating pressure in bar	Oil quantity in the tank / cylinder in ml. Standard oil HLP 32 other oils on request	Weight kg
	Maximum stroke in mm	Maximum lifting load with the lifting head in kg	Maximum lifting load with lifting claw in kg	Dimensions in mm L x B x H
A	Insertion height in mm	LH	Useable length of lifting claw in mm	#V Adjustment positions Distances in mm